

聚氨酯双向格莱圈 W3-6A



截面图	材料	温度范围	压力	速度	特点	标识									
	PU+橡胶	-30至100	≤40	≤0.5	双向作用, 摩擦力小, 标准化, 通用性强	W3-6AN									
D1	d1	L1	D1	d1	L1	D1	d1	L1	D1	d1	L1	D1	d1	L1	
8	3.1	2.2	50	34.5	6.3	110	99	4.2	230	214.5	6.3	700	672	9.5	
10	5.1	2.2	50.8	43.3	3.2	110	94.5	6.3	230	209	8.1	710	682	9.5	
12	7.1	2.2	50.8	39.8	4.2	110	89	8.1	240	219	8.1	740	712	9.5	
14	9.1	2.2	52	41	4.2	115	99.5	6.3	250	229	8.1	780	752	9.5	
15	7.5	3.2	53	42	4.2	120	109	4.2	250	225.5	8.1	800	772	9.5	
16	11.1	2.2	55	44	4.2	120	104.5	6.3	250	134.5	6.3	900	872	9.5	
16	8.5	3.2	57	46	4.2	120	99	8.1	254	233	8.1	1000	972	9.5	
18	13.1	2.2	58	47	4.2	125	114	4.2	260	239	8.1	1000	962	13.8	
18	10.5	3.2	60	49	4.2	125	109.5	6.3	265	244	8.1	1050	1022	9.5	
19.05	11.55	3.2	62	51	4.2	125	104	8.1	268	247	8.1	1065	1027	13.8	
20	15.1	2.2	63	52	4.2	127	111.5	6.3	270	249	8.1	1070	1032	13.8	
20	12.5	3.2	63	47.5	6.3	130	114.5	6.3	280	259	8.1	1200	1172	9.5	
21	13.5	3.2	65	54	4.2	130	109	8.1	290	269	8.1	1200	1162	13.8	
22	17.1	2.2	68	57	4.2	132	121	4.2	300	279	8.1	1225	1187	13.8	
22	14.5	3.2	70	59	4.2	135	114	8.1	300	275.5	8.1	1500	1462	13.8	
24	16.5	3.2	70	54.5	6.3	140	124.5	6.3	304.8	283.8	8.1	2000	1962	13.8	
25	20.1	2.2	75	64	4.2	140	119	8.1	310	289	8.1	2700	2662	13.8	
25	17.5	3.2	75	59.5	6.3	145	129.5	6.3	320	299	8.1				
25	14	4.2	80	69	4.2	145	124	8.1	320	295.5	8.1				
25.4	20.5	2.2	80	64.5	6.3	150	134.5	6.3	330	305.5	8.1				
28	20.5	3.2	80	59	8.1	150	129	8.1	340	315.5	8.1				
30	22.5	3.2	82.5	67	6.3	155	134	8.1	350	325.5	8.1				
32	27.1	2.2	85	69.5	6.3	160	144.5	6.3	360	335.5	8.1				
32	24.5	3.2	85	64	8.1	160	139	8.1	370	345.5	8.1				
32	21	4.2	90	79	4.2	165	144	8.1	380	355.5	8.1				
35	27.5	3.2	90	74.5	6.3	170	149	8.1	400	375.5	8.1				
35	24	4.2	90	69	8.1	175	154	8.1	420	395.5	8.1				
36	28.5	3.2	95	84	4.2	180	164.5	6.3	430	405.5	8.1				
38	30.5	3.2	95	79.5	6.3	180	159	8.1	440	415.5	8.1				
40	32.5	3.2	95	74	8.1	190	169	8.1	450	425.5	8.1				
40	29	4.2	100	89	4.2	194	178.5	6.3	460	435.5	8.1				
42	31	4.2	100	84.5	6.3	200	184.5	6.3	480	455.5	8.1				
44.45	36.95	3.2	100	79	8.1	200	179	8.1	500	475.5	8.1				
45	34	4.2	101.6	86.1	6.3	205	184	8.1	555	530.5	8.1				
48	37	4.2	105	94	4.2	210	189	8.1	600	575.5	8.1				
50	42.5	3.2	105	89.5	6.3	215	194	8.1	640	615.5	8.1				
50	39	4.2	108	92.5	6.3	220	199	8.1	660	635.5	8.1				

聚氨酯双向格莱圈 W3-6B



截面图			材料	温度范围	压力	速度	特点	标识
			PU + 橡胶	-40至100	≤30	≤0.5	双向作用，摩擦力小，标准化，通用性强	W3-6BN
D1	d1	L1	D1	d1	L1	D1	d1	L1
0.561	0.315	0.185	4.625	4.250	0.280			
0.686	0.440	0.185	5.000	4.626	0.280			
0.811	0.565	0.185	5.500	5.021	0.365			
1.062	0.816	0.185	6.000	5.521	0.365			
1.125	0.879	0.185	6.000	5.521	0.579			
1.187	0.941	0.185	6.500	6.020	0.365			
1.250	1.004	0.185	7.000	6.520	0.365			
1.375	1.129	0.185	7.500	7.020	0.365			
1.500	1.254	0.185	7.750	7.270	0.365			
1.500	1.254	0.304	8.000	7.520	0.365			
1.625	1.374	0.185	8.250	7.770	0.365			
1.750	1.504	0.185	8.500	8.020	0.365			
1.750	1.504	0.304	9.000	8.520	0.365			
1.875	1.500	0.280	9.500	9.020	0.365			
2.000	1.625	0.280	10.000	9.520	0.365			
2.000	1.625	0.424	10.500	10.020	0.365			
2.250	1.875	0.280	11.000	10.520	0.365			
2.375	2.000	0.280	11.500	11.020	0.365			
2.500	2.125	0.280	12.000	11.520	0.365			
2.500	2.125	0.424	14.000	13.520	0.365			
2.750	2.374	0.280						
2.749	2.374	0.424						
3.000	2.624	0.280						
3.000	2.624	0.424						
3.250	2.874	0.280						
3.375	3.000	0.280						
3.500	3.125	0.280						
3.500	3.125	0.424						
3.625	3.250	0.280						
3.750	3.375	0.280						
3.875	3.500	0.280						
4.000	3.625	0.280						
4.000	3.625	0.424						
4.250	3.875	0.280						
4.500	4.125	0.280						

聚氨酯双向格莱圈 W3-6C



截面图			材料	温度范围	压力	速度	特点	标识						
			PU + 橡胶	-40至100	≤30	≤0.5	双向作用，摩擦力小，标准化，通用性强	W3-6CN						
D1	d1	L1	D1	d1	L1	D1	d1	L1	D1	d1	L1	D1	d1	L1
1.500	1.258	0.275												
1.750	1.500	0.185												
2.000	1.625	0.280												
2.000	1.625	0.394												
2.250	1.875	0.280												
2.375	2.000	0.280												
2.500	2.125	0.280												
2.500	2.125	0.410												
2.750	2.375	0.280												
3.000	2.380	0.250												
3.000	2.625	0.280												
3.000	2.625	0.410												
3.250	2.875	0.280												
3.500	3.125	0.280												
3.500	3.125	0.410												
3.750	3.375	0.280												
4.000	3.625	0.280												
4.000	3.625	0.410												
4.250	3.875	0.280												
4.500	4.125	0.280												
4.625	4.250	0.280												
5.000	4.625	0.280												
5.000	4.528	0.538												
5.500	5.020	0.365												
6.000	5.520	0.365												
6.000	5.520	0.538												
6.500	6.020	0.365												
7.000	6.520	0.365												
7.500	7.020	0.365												
8.000	7.520	0.365												
8.500	8.020	0.365												
9.000	8.520	0.365												

聚氨酯双向格莱圈 W3-6D



截面图	材料	温度范围	压力	速度	特点	标识					
	PU+橡胶	-40至100	≤30	≤0.5	双向作用，摩擦力小，标准化，通用性强	W3-6DN					
D1	d1	L1	D1	d1	L1	D1	d1	L1	D1	d1	L1
1.500 +0.006/-0	1.000 +0.006/-0	0.394									
1.500 +0.004/-0	1.125 +0.004/-0	0.263									
1.500 +0.003/-0	1.250 +0.003/-0	0.196									
1.750 +0.006/-0	1.250 +0.006/-0	0.394									
1.750 +0.004/-0	1.375 +0.004/-0	0.263									
1.750 +0.004/-0	1.375 +0.004/-0	0.526									
2.000 +0.006/-0	1.500 +0.006/-0	0.394									
2.000 +0.004/-0	1.625 +0.004/-0	0.328									
2.000 +0.004/-0	1.625 +0.004/-0	0.394									
2.250 +0.004/-0	1.875 +0.004/-0	0.328									
2.500 +0.004/-0	2.000 +0.004/-0	0.394									
2.500 +0.004/-0	2.125 +0.004/-0	0.328									
2.500 +0.004/-0	2.125 +0.004/-0	0.394									
2.750 +0.004/-0	2.375 +0.004/-0	0.328									
3.000 +0.006/-0	2.500 +0.006/-0	0.394									
3.000 +0.006/-0	2.500 +0.006/-0	0.550									
3.000 +0.004/-0	2.625 +0.004/-0	0.328									
3.000 +0.004/-0	2.625 +0.004/-0	0.394									
3.250 +0.004/-0	2.750 +0.004/-0	0.577									
3.250 +0.004/-0	2.875 +0.004/-0	0.328									
3.500 +0.006/-0	3.000 +0.006/-0	0.394									
3.500 +0.004/-0	3.125 +0.004/-0	0.328									
3.500 +0.004/-0	3.125 +0.004/-0	0.394									
3.750 +0.004/-0	3.375 +0.004/-0	0.328									
4.000 +0.006/-0	3.500 +0.006/-0	0.394									
4.000 +0.004/-0	3.625 +0.004/-0	0.394									
4.500 +0.006/-0	4.000 +0.006/-0	0.394									
4.500 +0.004/-0	4.000 +0.004/-0	0.591									
5.000 +0.006/-0	4.375 +0.006/-0	0.526									
5.000 +0.006/-0	4.500 +0.006/-0	0.394									
5.000 +0.006/-0	4.500 +0.006/-0	0.526									
5.000 +0.006/-0	4.500 +0.006/-0	0.591									
5.250 +0.006/-0	4.750 +0.006/-0	0.591									
5.500 +0.006/-0	5.000 +0.006/-0	0.394									
6.000 +0.006/-0	5.500 +0.006/-0	0.394									
6.000 +0.006/-0	5.500 +0.006/-0	0.591									
6.500 +0.006/-0	6.000 +0.006/-0	0.591									