

凹槽星形格莱圈 W3-5



截面图			材料	温度范围	压力	速度	特点	标识			
			PTFE + 橡胶	NBR -30至100 FKM -20至200	≤40	≤2	双向作用，摩擦力小，标准化，分隔介质，无爬行	W3-5N W3-5F			
D1	d1	L1	D1	d1	L1	D1	d1	L1	D1	d1	L1
1.500	+0.004/-0	0.884	0.288/0.293								
2.000	+0.004/-0	1.384	0.288/0.293								
2.225	+0.004/-0	1.630	0.288/0.293								
2.500	+0.004/-0	1.884	0.288/0.293								
3.000	+0.004/-0	2.384	0.288/0.293								
3.250	+0.004/-0	2.634	0.288/0.293								
3.500	+0.004/-0	2.884	0.288/0.293								
4.000	+0.004/-0	3.384	0.288/0.293								
4.500	+0.004/-0	3.884	0.288/0.293								
5.000	+0.004/-0	4.384	0.288/0.293								
5.500	+0.005/-0	4.660	0.375/0.380								
6.000	+0.005/-0	5.160	0.375/0.380								
6.500	+0.005/-0	5.660	0.375/0.380								
7.000	+0.005/-0	6.170	0.375/0.380								
8.000	+0.005/-0	7.170	0.375/0.380								