



| 代号 | 名称 | 截面图 | 材料 | 压力 | 温度 | 速度 | 特点 | | | | | | | |
|----|-------|-----|-------|-----|---------|-----|-------|----|-----|-----|----|-----|-----|----|
| T4 | 往复用油封 | | 骨架+橡胶 | 0.5 | -30至100 | 1.5 | 往复运动用 | | | | | | | |
| d | D | H | d | D | H | d | D | H | d | D | H | d | D | H |
| 8 | 18 | 7 | 25 | 40 | 8 | 45 | 68 | 12 | 70 | 88 | 12 | 120 | 150 | 14 |
| 10 | 20 | 7 | 25 | 45 | 10 | 45 | 68 | 12 | 70 | 95 | 14 | 120 | 150 | 14 |
| 12 | 25 | 7 | 28 | 45 | 8 | 48 | 70 | 12 | 75 | 95 | 10 | 125 | 150 | 14 |
| 14 | 24 | 7 | 28 | 45 | 8 | 48 | 70 | 12 | 75 | 100 | 14 | 125 | 155 | 14 |
| 15 | 30 | 10 | 28 | 48 | 11 | 50 | 68 | 9 | 78 | 100 | 13 | 130 | 155 | 14 |
| 16 | 30 | 7 | 30 | 50 | 11 | 50 | 72 | 12 | 80 | 100 | 14 | 140 | 165 | 14 |
| 16 | 32 | 10 | 30 | 50 | 11 | 52 | 75 | 12 | 80 | 105 | 14 | 145 | 175 | 14 |
| 17 | 38 | 7 | 32 | 52 | 11 | 55 | 72 | 9 | 80 | 110 | 13 | 150 | 180 | 14 |
| 18 | 35 | 11 | 35 | 52 | 12 | 55 | 78 | 12 | 85 | 110 | 14 | 150 | 180 | 14 |
| 20 | 35 | 7 | 35 | 55 | 11 | 55 | 80 | 14 | 90 | 115 | 14 | 160 | 185 | 14 |
| 20 | 35 | 7 | 36 | 52 | 11 | 60 | 78 | 9 | 95 | 120 | 13 | 160 | 190 | 14 |
| 20 | 40 | 10 | 38 | 55 | 8 | 60 | 82 | 12 | 100 | 125 | 14 | 190 | 215 | 14 |
| 22 | 38 | 8 | 38 | 60 | 12 | 60 | 82 | 14 | 105 | 135 | 14 | 220 | 245 | 14 |
| 22 | 40 | 10 | 40 | 55 | 9 | 65 | 88 | 12 | 110 | 135 | 14 | 230 | 270 | 20 |
| 22 | 42 | 11 | 40 | 62 | 12 | 65 | 90 | 14 | 110 | 140 | 14 | 250 | 290 | 20 |
| 25 | 38 | 7 | 40 | 62 | 12 | 68 | 95 | 13 | 120 | 145 | 14 | | | |