



装配例

型式例

截面图	材料	温度范围	压力	速度	特点	代号
	PU	-35至100	≤ 1.6	≤ 1	对中性好	QH1
	NBR	-20至100				

d	D	H	D1	D2	L	d	D	H	D1	D2	L
4.5	8	3.5	5	6.5	3.1	22	30	7.8	23	26	7
5	9	4.1	5.5	7	3.7	25	33	6	28.5	29	7
6	10	4.1	6.5	8	3.7	25	33	7.8	26	29	7
6	12	5.5	8.6	9	7	28	36	6	31.5	32	7
8	11.6	3.5	8.5	10	3.3	28	36	7.8	29	32	7
8	16	6	44.5	13	7	30	40	6	34.5	35	7
9.5	15	4.6	10	12	4.5	30	40	7.8	31.5	35	7
10	18	6	13.5	15	7	32	42	6	36.5	37	7
10	18	7.8	10.5	15	7	32	42	7.8	33.5	37	7
12	18	5	13	15.5	4.8	36	46	6	40.5	41	7
12	20	6	15.5	17	7	36	46	7.8	37.5	41	7
12	20	7.8	13	17	7	40	50	6	44.5	45	7
14	22	5.5	15	18.5	5.2	40	50	7.8	41.5	45	7
14	22	6	17.5	19	7	50	60	7.8	51.5	55	7
14	22	7.8	15	19	7	50	67	10	54	58	12.5
16	22	5.5	17	19.5	5.2	50	67	11	53	58	12.5
16	24	6	19.5	21	7	52	69	10	56	60	12.5
16	24	7.8	17	21	7	57	74	10	61	65	12.5
18	26	6	21.5	23	7	57	74	11	60	65	12.5
18	26	7.8	19	23	7	70	87	10	74	78	12.5
20	28	6	23.5	24	7	70	87	11	73	78	12.5
20	28	7.8	21	24	7	78	95	11	81	86	12.5
22	30	6	25.5	26	7	78	98	10	82.5	86	12.5